

PORTABLE SAW MACHINES




PORTABLE SAW MACHINES

GS86.....	B2
ECO 92.....	B3
SUPERECO 98.....	B4




Three models to meet the needs of even those who favor machines with extremely compact cutting specifications and machine dimensions/weight and low weight; whose spearhead is the GS86: the super-professional compact saw machine which is an exceptional allied especially when wall coverings.






AVAILABLE BLADES



PACKAGE



TECHNICAL CHARACTERISTICS



- For cutting porcelain, single-double fired, marble, granite. Straight, 45° bevel (Jolly) cuts, square e round knockouts, sanding/polishing.
- Unlimited size of cut.
- Maximum thickness of cut: 25 mm (1") in single pass; 50 mm (2") in double pass.
- Maximum disc: Ø 115 mm (4 1/2"); smallest blade: Ø 100 mm (4").
- Gear ratio of motor to disc 1 ÷ 2.1. Drive belt type Z90.

- The blade is cooled via heavy duty pump.
- Supplied with: turbo blade Ø 115 mm (4 1/2") for tiles, 5 abrasive discs for polishing/sanding, key kit, dressing stone, user and maintenance manual.
- Turtle shell cover helps to prevent damage when not in use.

MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	M	Motor	Motor	Disc	Disc	
125INOX F	8024648003584	1	230 V 50 Hz	Single-phase	0,9 HP / 0,65 kW	2800	115 mm	4 1/2"	5800
125INOX 60	8024648017055	1	230 V 60 Hz	Single-phase	0,9 HP / 0,65 kW	3360	115 mm	4 1/2"	7000
125INOX US	8024648009265	1	110 V 60 Hz	Single-phase	0,9 HP / 0,65 kW	3360	115 mm	4 1/2"	7000
125INOX GB	8024648009258	1	110 V 50 Hz	Single-phase	0,9 HP / 0,65 kW	2800	115 mm	4 1/2"	5800

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT

Model	Disc	Thickness	Width	Height	Depth	Width	Depth	Weight	Dimensions	Weight	Dimensions	Weight
GS86	100 mm 115 mm	4" 4 1/2"	18 mm 25 mm	25/32" 1"	10 mm 10 mm	4" 4"	∞ ∞	∞	45x45xh 30 cm 18"x18"xh 12"	25 Kg 55.1 lbs	50x50xh 35 cm 20"x20"xh 13	26 Kg 57.3 lbs






PORTABLE SAW MACHINES



AVAILABLE BLADES



CONTINUAL CROWN DISC

TURBO DISC

OPTIONAL




45° SLIDING SQUARE

PACKAGE



CARTON BOX

TECHNICAL CHARACTERISTICS



Ø 200mm

Ø 25,4mm

FOLDING BENCH

DIRECT DRIVE

90° SQUARE

WET COOLING

- For cutting single-double fired and porcelain. Straight cuts and 45° bevel (Jolly).
- Unlimited size of cut.
- Maximum thickness of cut: 20 mm (13/16") in single pass; 40 mm (1 5/8") in double pass.
- Maximum disc: Ø 150 mm (6").
- Blade is cooled through immersion in the water reservoir.

- Tilting table for bevel cuts from 0° to 47°.
- Supplied with: continuous rim blade for tiles Ø 150 mm (6"), key kit, dressing stone, user and maintenance manual.

MODEL SPECIFICATIONS

Part No.								
370 DF	8024648003607	1	230 V 50/60 Hz	Single-phase	0,9 HP / 0,65 kW	2800/3360	200 mm 8"	2800/3360
370 USA	8024648010384	1	110 V 60 Hz	Single-phase	0,9 HP / 0,65 kW	3360	200 mm 8"	3360
370 GB	8024648009289	1	110 V 50 Hz	Single-phase	0,9 HP / 0,65 kW	2800	200 mm 8"	2800


CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT

Model										
ECO 92	200 mm 8"	36 mm 1 3/8"	40 mm 1 5/8"	∞	∞	∞	47x45xh 27 cm 18 1/2"x18"xh 10 5/8"	16 Kg 35.3 lbs	50x50xh 32 cm 20"x20" xh 13"	17 Kg 37.5 lbs





AVAILABLE BLADES




OPTIONAL



PACKAGE



TECHNICAL CHARACTERISTICS



- For cutting single-double fired and porcelain. Straight cuts and 45° bevel (Jolly).
- Unlimited size of cut.
- Maximum thickness of cut: 20 mm (13/16") in single pass; 40 mm (1 5/8") in double pass.
- Maximum disc: Ø 150 mm (6").

- Blade is cooled through immersion in the water reservoir.
- Tilting table for bevel cuts from 0° to 47°.
- Supplied with: continuous rim blade for tiles Ø 150 mm (6"), key kit, dressing stone, user and maintenance manual.

MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	M	Motor	Motor	Disc	Disc	
378 98	8024648003621	1	230 V 50/60 Hz	Single-phase	0,5 HP / 0,37 kW	2800/3360	150 mm	6"	2800/3360
378 USA	8024648008824	1	110 V 60 Hz	Single-phase	0,33 HP / 0,24 kW	3360	150 mm	6"	3360
378 GB	8024648008800	1	110 V 50 Hz	Single-phase	0,33 HP / 0,24 kW	2800	150 mm	6"	2800

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT

Model	Disc	Thickness	Thickness	∞	∞	∞	Machine	Weight	Dimensions	Weight
SUPERECO 98	150 mm 6"	20 mm 13/16"	30 mm 1 3/16"	∞	∞	∞	45x42xh 22 cm 17 3/4"x16 1/2"xh 8 5/8"	11 Kg 24 lbs	50x45xh 30 cm 19 5/8"x17 3/4"xh 11 7/8"	12 Kg 26 lbs

